






Frame Ends - Steel
















 <p>Ritchey Cast Ends. 62°. For 13.5mm. Chainstay, 12.5mm. Seat Stay Socket.</p>	<p>Machined Front Ends.</p> <p>For all of these Fork Blade abutment * is 14.4mm:</p> <p>FE1491. 11.4mm. Plug.</p> <p>FE1490S 10.7mm. Plug FE1491S 11.7mm. Plug FE1490S IX 10.7mm. Plug. Stainless. FE1491S IX 11.7mm. Plug. Stainless.</p>
<p>Forged. Front Ends. No Eye</p>  <p>Forged. Single eye. Offset - 62°. Available without eye in 53 or 62°.</p>  <p>Forged. Single eye - 53,62,74°. Extra strong.</p>	<p>BSE External Fork Ends. 13mm. ID Socket</p>  <p>SILVA</p>  <p>Art. 570. 10.7mm. Plug. 13.25mm. Abutment *.</p> <p>Art. 569. External. 13.25mm ID Socket.</p>



Cast Frame Ends








* Dimensions quoted for internal plug in ends, show the internal plug diameter as well as the outer diameter for the step up against which the frame tube will abutt.

-----Articulated angle-----

 <p>LR09R-1. For Seat Stay Tip 10.5mm. Chain Stay Tip 12.5mm. Angle: 72°.</p> <p>SLR09R-1. As above - Stainless.</p>	 <p>LR12-1. Angles - 72 & 75°. For 12.5mm. S/S. 12.5mm. C/S. Also 72°. 12.5mm. S/S. 13.2mm. C/S.</p> <p>SLR12-1. Stainless - 72°. 12.5mm. S/S. 12.5mm. C/S.</p> <p>LR13M-1. ATB. 63°. For 12.5mm. S/S 12.5mm. C/S Tip Also 14mm. C/S Tip</p>	 <p>LR01. For Seat Stay Tip 12.5mm. For C/Stay Tip 14mm. Articulated angle.</p>	 <p>LR10R. Articulated angle. For Seat stay dia. 10.5mm. Tip For Chain stay dia. 12.5mm. Tip</p>	 <p>LR302R. For 12.5mm. C/S. Tip 10.5mm. S/S. Tip Available as stainless in set with other Fleur De Lys Parts</p>
 <p>LR15 CAST TRACK ENDS 10.85/12.85mm *. Seat Stay Plug. 11.5/13.7mm *. Chain Stay Plug.</p>	<p>LE17H. Inner Socket 13mm.</p>  <p>LE09. Diameter. 10.5/12.7mm *.</p>  <p>LE20. Diameter. 12/14.3mm *.</p> 	<p>LE21. 14mm Socket.</p>  <p>LE20-2. Plug 12/14.3mm *.</p> <p>SLE20-2. As Above but Stainless.</p> 	<p>LE16. For 25.4mm.OD Fork Tip. Diameter. 23/25.4mm *.</p>  <p>LE13-1. To fit 28.6mm. diameter. tubes. 26.2mm. plug.</p> 	<p>LE-MAX</p>  <p>Plug insert shaped to fit Max Blades fully profiled to the bottom. 34.4x17.4mm. Teardrop plug.</p>  <p>LE302R. 12.5mm. ID. Available as stainless in set with other Fleur De Lys Parts</p>

EVEREST

Cast Frame Ends.

 <p>FC01. Racing Ends. For 12.5mm. C/S Tip. For 12.5mm. S/S Tip.</p>	 <p>C-111. Rear Ends. Extra Strong. Free Angle. For 13.5mm. Chainstay Tip.</p>	 <p>C1152. Articulated angle. 8.9/11mm Seat Stay Plug *. 11/13mm Chain Stay Plug *.</p>	 <p>C101. 9.8/13mm. Plug *.</p>	<p>For 22.2mm. OD Tip Fork Blade ends (available):</p>  <p>C196. 19.4mm. Plug.</p>  <p>C188. 19mm. Plug. For Straight tubes.</p>	 <p>C132. Stainless Steel Derailleur hanger.</p>
----------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------